

ALL STEEL CONSTRUCTION. THE STRONGEST CONVEYORS IN THE WORLD.

NESTAFLEX[®]

SMART DESIGNS COME FROM SMART SOLUTIONS.



Nestaflex 375 truck loading system featured with herringbone transition and guide track system.



4-Point Leg Connection

NESTAFLEX 375

The ALL-BOLTED Nestaflex 375 is designed for use in **high-volume** shipping and receiving applications, especially distribution centers. This exceptional conveyor is application specific to meet individual material handling requirements. The 375 is a heavy duty, self tracking gravity skate wheel conveyor that has a per lineal foot capacity of 375 pounds! The ALL-BOLTED steel frame construction and rugged 4 point leg connection provide the structural integrity and durability needed for today's most demanding applications!

NESTAFLEX[®]
FLEXIBLE CONVEYORS

375



GRAVITY SKATE WHEEL CONVEYOR

NESTAFLEX 375 TRUCK LOADING SYSTEM

The Nestaflex 375 is the leading expandable conveyor for outbound product and can be equipped with several engineered options to maximize performance. Fixed height perpendicular legs make sure your conveyor pitch remains constant and provides gravity flow, while the **Herringbone Transition** centers your product as it goes from your fixed conveyor to the truck loading system. Storage is made simple by the **Guide Track System** designed to allow you to store the 375 under your fixed conveyor to maximize control and storage space.

NESTAFLEX 375 RECEIVING SYSTEM

The Nestaflex 375 is also the conveyor of choice for your high volume receiving applications. Larger casters help move the conveyor easily over dock plates. The optional receiving impact conveyor can be built into your system to help add longevity to the overall system and reduces maintenance issues. We encourage you to take advantage of our free application analysis to determine the operational efficiencies that can be gained from the **Nestaflex 375 and the flexible material handling-smart solutions team.**

CONVEYOR OPTIONS



Herringbone Transition



Impact Conveyor



Powered Assist



8 x 2 caster

INSTALLATION

We also offer custom installation from our factory trained technicians!

Flexible Material Handling

SMART SOLUTIONS[™]

www.flexmh.com

800-669-1501



SMART DESIGNS COME FROM SMART SOLUTIONS.

SPECIFICATIONS

18" WIDTHS		24" WIDTHS		30" WIDTHS		LENGTH ADJUSTMENTS WITH 5 1/4" AXLE CENTERS		
Model 375	Skate Wheels Per Axle	Model 375	Skate Wheels Per Axle	Model 375	Skate Wheels Per Axle	Contracted/ Extended	Leg Sets Per Unit	Bed Sections Per Unit
37518008	6	37524008	9	37530008	12	2' 7" - 8' 6"	3	2
37518012	6	37524012	9	37530012	12	3' 7" - 12' 2"	4	3
37518016	6	37524016	9	37530016	12	4' 8" - 15' 10"	5	4
37518020	6	37524020	9	37530020	12	5' 8" - 19' 6"	6	5
37518024	6	37524024	9	37530024	12	6' 8" - 23' 2"	7	6
37518028	6	37524028	9	37530028	12	8' 2" - 28' 0"	8	7
37518032	6	37524032	9	37530032	12	9' 2" - 31' 8"	9	8
37518036	6	37524036	9	37530036	12	10' 3" - 35' 4"	10	9
37518040	6	37524040	9	37530040	12	12' 1" - 41' 10"	12	11
37518044	6	37524044	9	37530044	12	13' 1" - 45' 6"	13	12
37518048	6	37524048	9	37530048	12	14' 4" - 49' 5"	14	13
37518052	6	37524052	9	37530052	12	15' 4" - 53' 1"	15	14
37518056	6	37524056	9	37530056	12	16' 5" - 56' 9"	16	15
37518060	6	37524060	9	37530060	12	17' 5" - 60' 5"	17	16

Also available in 36" widths.

NESTAFLEX 375 STANDARD FEATURES AND OPTIONS

NESTAFLEX
FLEXIBLE CONVEYORS

375

SKATE WHEEL OPTIONS



P-Black Polymer



S-Steel

CONSTRUCTION

All-steel BOLTED construction.

CONVEYOR FORMATS

Available in 18", 24" and 30" widths. 36" available upon request. Lengths can be tailored to your specific application.

SKATE WHEEL OPTIONS

P-Black Polymer with 7 steel ball bearings in a captive race provides superior wheel rotation.

S-Steel skate wheel with steel ball bearings for impact resistant, moderate to high volume usage.

HEIGHT ADJUSTMENT

Preset individual leg heights are application specific. To maintain gravity flow, a pitch of 5/16 per foot is recommended. Conveyor height is engineered to your specific application.

LEGS

Zinc plated 1 1/8 O.D. 12 gauge steel tubing with reinforced inner leg and double cross braces. Four point bolted leg connection to skate wheel axles and side links.

HEAVY DUTY CASTERS

Standard 6"x 2" casters with heavy duty stem. Casters with swivel/wheel lock pedal brakes are provided on the first and last legs. 8" x 2" casters available for added strength and mobility.

SIDE LINKS

Conveyor side links are made of 7 gauge steel and feature bolted construction.

COUPLERS

Couplers are standard. Optional universal connectors are available to couple to other extendable conveyor brands.

BOX STOP/HANDLE

Standard retractable package stop serves also as an ergonomic handle.

AXLES

5/16" diameter axles. Standard axle centers are 5 1/4", 4" and 3" are available for smaller cartons.

WARRANTY

Two year factory warranty.

Flexible Material Handling

SMART SOLUTIONS™

www.flexmh.com
800-669-1501